



WELL FLOOR

SPC FLOORING
CLICK SYSTEM
100% VIRGIN MATERIAL

4mmx0.3mm





SPC FLOORING CLICK SYSTEM
100% VIRGIN MATERIAL 4mmx0.3mm
180mm x 1220mm



1001-15



1002-5



1018-2



1050-8

SPC FLOORING CLICK SYSTEM
100% VIRGIN MATERIAL 4mmx0.3mm
180mm x 1220mm



7181



7242-2



7274-1



7284-1

SPC FLOORING CLICK SYSTEM
100% VIRGIN MATERIAL 4mmx0.3mm
180mm x 1220mm



7310-2



7310-4



7365-8



7365-13

SPC FLOORING CLICK SYSTEM
100% VIRGIN MATERIAL 4mmx0.3mm
180mm x 1220mm



19018-1



SPC FLOORING CLICK SYSTEM 100% VIRGIN MATERIAL



Waterproof



Anti-Termite



Scratch Resistant



Easy to Install



**Abrasion
Resistance**



Easy to Clean



**Comfortable
Underfoot**



Slip Resistance

SPECIFICATIONS:	
ITEM:	SPC Flooring click system 100% virgin material
DIMENSION:	180mm x 1220mm
TOTAL THICKNESS:	4.0mm
PACKAGING:	14pcs/ 3.0744m ² per box
SURFACETEXTURE:	
WEAR LAYER:	0.30mm

Test Parameter

CHARACTERISTICS	TEST METHOD	RESULT
Dimension	EN 427	
Thickness-Overall	EN 428	4.0mm
Thickness-Wear Layer	EN 429	0.30mm
Peeling strength of layers	EN 431	Pass
Shear forces of layers	EN 432	Good
Residual indentation after static load	EN 433	Mean value 0.01mm
Dimension Stability	EN 434	Shrinkage 0.002%, Curling 0.2mm
Flexibility-10mm mandrel	EN 435	No Damage
Resistance to chemicals	EN 423	Class
Bearing a castor chair	EN 425	No disturbance No delamination
Color fastness to light	ISO 105 B02	>=6
Wear resistance	EN660	Pass
Toxic	EN71-3	Complies
Resistance to fire	ASTM E84-03	NFPA Class B
Performance classification	DIN 51130	R9
Performance classification	EN685	23,34,43
GB/T 4085 GB 8624 B1		Pass
CNS8907		Pass

CITRA ALADDIN SDN BHD

LOT 3687 BLOCK B, BATU 4 1/2, JALAN
SEGAMPUT, 51200 KUALA LUMPUR, MALAYSIA

OFFICE: | MOBILE:

EMAIL: | WEBSITE:

